

SPECIFICATIONS

WFA Platinum Inline Water Filter System

K-B-PLATINUM

Now offers improved sediment and limescale reduction and increased capacity.

Proprietary filter head technology:
filter cartridge warranted to fit and compatible with all existing Platinum installations.



AS3497

Lic.WMKA22045
IAPMO R&T OCEANA



ANSI/NSF STANDARDS
42 AND 53



MADE IN
USA



ASSEMBLED IN
AUSTRALIA

WaterFilters
AUSTRALIA

WFA Platinum Inline Water Filter System

K-B-PLATINUM

SPECIFICATIONS

Service life/change cartridge	12 months*
Working Pressure	10–175psi (70–1200 kPa)
Temperature	2–38°C
Height to allow for cartridge change	460mm
Width of filter head/cartridge	225mm
Flow Rate	up to 8 litres per minute
Micron Rating	1 micron cyst rated
Burst pressure	exceeds 3,500 kPa as tested by CSIRO
Warranty	10 years

*Service life will vary according to flow rate, influent line pressure and local water conditions.

INCLUSIONS

- WFA Filter Head with Mounting Bracket
- Dual Check Valve
- Pex Hose 550mm ½" female to ¾" male
- Brass Hex Nipple ¾" male to ½" male
- Filter Alarm
- Plumbing Tape
- WFA Platinum Cartridge
- Stabilizing Bracket
- Mounting Screws
- Owners Manual


CARTRIDGE RE-ORDER CODE

C-B-PLATINUM

PERFORMANCE

- Certified to remove/reduce:
- Sediment and rust particles
 - Chlorine
 - Bad taste and odours
 - Limescale
 - Cysts including Giardia and Cryptosporidium
 - Does not remove fluoride, natural minerals & salts

VERTICAL OR HORIZONTAL INSTALLATION



To find out more call us on 02 9905 6211
Or if you prefer, you can email us at sales@wfa.com.au

WaterFilters
AUSTRALIA