

SPECIFICATIONS

WFA Vanity Inline Water Filter System

K-B-VANITY

New and unique filter system for the bathroom vanity.

Compact, propriety filter system.



AS3497

Lic.WMKA22045
IAPMO R&T OCEANA



ANSI/NSF
STANDARD 42



MADE IN
USA



ASSEMBLED IN
AUSTRALIA

WaterFilters
AUSTRALIA

WFA Vanity Inline Water Filter System

K-B-VANITY

SPECIFICATIONS

Service life/change cartridge	12 months*
Working Pressure	10–175psi (70–1200 kPa)
Temperature	2–38°C
Height to allow for cartridge change	335mm
Width of filter head/cartridge	225mm
Flow Rate	up to 8 litres per minute
Burst pressure	exceeds 3,500 kPa as tested by CSIRO
Warranty	10 years

*Service life will vary according to flow rate, influent line pressure and local water conditions.

INCLUSIONS

- WFA Filter Head with Mounting Bracket
- WFA Vanity Cartridge
- Mounting Screws
- Dual Check Valve
- Pex Hose 550mm 1/2" female to 3/8" male
- Brass Hex Nipple 3/8" male to 1/2" male
- Filter Monitor Alarm
- Plumbing Tape
- Owners Manual

PERFORMANCE

Certified to remove/reduce:


- Sediment
- Chlorine
- Bad taste and odours
- Limescale

CARTRIDGE RE-ORDER CODE

C-B-VANITY

To find out more call us on 02 9905 6211
Or if you prefer, you can email us at sales@wfa.com.au

VERTICAL OR HORIZONTAL INSTALLATION



WaterFilters
AUSTRALIA